

Integrated Sterilizer & Shredder



Model ISS	ISS 25L	ISS AC-575	ISS 500
Chamber dimensions Inner dia. x Depth	260 x 482 mm	500 x 800 mm	840 x 923 mm
Chamber volume	25 l	150 l	560 l
External dimensions W x H x D	1070 x 1025 x 725 mm	1290 x 2150 x 2039 mm	with housing W x H x D: 2710 x 2030 x 2300 mm with autoloader W x H x D: 2710 x 2900 x 2800 mm
Approximate weight	280 kg	880 kg	1500 kg
Average processable waste kg/h	5-7,5 kg/h *	45-67 kg/h *	100-150 kg/h *
Power supply**	3-Ph. 380-400 V, 50/60 Hz		
Power with steam generator	12 kW	36 kW	110 kW
Available sterilization cycles	Waste 134 °C / Textiles no Cut 134 °C / Special Waste 134 °C / Glass 134 °C		Waste 134 °C / Special Waste 134 °C / Glass 134 °C
Available test and other cycles	Dynamic test / Cleaning cycle		
Touch-screen display	LCD 5.7" Color Graphic		
Cover	Painted steel		
Chamber door	Automatic door locking system with advanced safety features		

* Depends on the density of the waste

** Adjustable to different voltage systems